

ENHANCED SURFACE PLASMON POLARITON PROPAGATION INDUCED BY ACTIVE DIELECTRICS

C. Athanasopoulos^{1,2}, M. Mattheakis^{1,2,*}, G. P. Tsironis^{1,2,3}

1) Crete Center for Quantum Complexity and Nanotechnology, Department of Physics, University of Crete, Heraklion, Greece; 2) Institute of Electronics Structure and Laser, Foundation for Research and Technology-Hellas; 3) School of Science and Technology, Nazarbayev University, Astana, Kazakhstan; *mariosmat@physics.uoc.gr

We present numerical simulations for the propagation of surface plasmon polaritons (SPPs) in a dielectric-metal-dielectric waveguide using COMSOL multiphysics software. We show that the use of an active dielectric with gain that compensates metal absorption losses enhances substantially plasmon propagation. Furthermore, the introduction of the active material induces, for a specific gain value, a root in the imaginary part of the propagation constant leading to infinite propagation of the surface plasmon. The computational approaches analyzed in this work can be used to define and tune the optimal conditions for surface plasmon polariton amplification and propagation.

References.

1. N. Economou, Surface plasmons in thin films, Phys. Rev., 182 No. 2 , 539-554 (1969).
2. L. Novotny, unedited chapters from the textbook L. Novotny and B. Hecht Principles of Nano-Optics. Cambridge University Press, Cambridge (2006).
3. S.A. Maier, Plasmonics: Fundamentals and Applications. Springer Science & Business Media LCC, New York (2007).
4. S.J. Orfanidis, Electromagnetic Waves and Antennas. Online book www.ece.rutgers.edu/~orfanidi/ewa/ (2008).